

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 1 of 10

Nylon 12 Tough

SECTION 1: Identification

Product Identifier

Product Name: Nylon 12 Tough **Product code:** FLP12T1001

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: For use in Formlabs Fuse Printers. **Uses Advised Against:** Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer: United States

Formlabs, Inc 35 Medford St Suite 201 Somerville, MA 02143 +1 617 855 0762 sds@formlabs.com

Emergency Telephone Number:

United States

CHEMTREC 1-800-424-9300 (24/7)

SECTION 2: Hazard(s) Identification

GHS Classification:

Combustible Dust

Label elements

Hazard Pictograms: None

Signal Word: Warning

Hazard statements:

Combustible Dust May form combustible dust concentrations in air.

Precautionary Statements: None

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: Trade Secret	Trade Secret	<99
CAS Number: Trade Secret	Trade Secret	<1

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 2 of 10

Nylon 12 Tough

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. If respiratory symptoms develop or persist, seek medical advice/attention.

Wash affected area with plenty of soap and water. Remove contaminated clothing and launder before reuse. If skin irritation develops or persists, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Product presents an explosion hazard when suspended in air under certain conditions. Inhalation of large amounts of dust may cause inflammation and irritation of the nose and throat. Symptoms may include cough, sore throat, tightness of the chest, chest pain and lightheadedness.

Delayed Symptoms and Effects:

Not determined or not applicable.

Immediate Medical Attention and Special Treatment

Specific Treatment:

Not determined or not applicable.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Dry chemical, sand and carbon dioxide.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

May form combustible dust concentrations in air. Reacts with water and alcohols. Reacts violently with oxidants, strong acids and bases and chlorinated hydrocarbons. This generates a fire and explosion hazard. Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 3 of 10

Nylon 12 Tough

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Violent reactions may result from the use of a water jet or halogenated extinguishing agents. When using extinguishers, avoid dispersing combustible dust into the air. Aim extinguishers directly at the base of the flames and apply the agent as gently as possible. Overall, give preference to using medium to wide spray patterns rather than solid streams. Use only non-sparking tools. Fire fight from a protected location or maximum possible distance. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Extinguish any sources of ignition. Do not ventilate area as this may spread dust. Wear recommended personal protective equipment including suitable respiratory protection (see Section 8). Ensure no sources of electric discharge or ignition are on your person before entering area. Do not get on skin, eyes or on clothing. Avoid breathing dust, fumes. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13). Avoid dust generation or stirring up of dust. Use only non-sparking tools. Ground all equipment used for

recovery and clean up. Vacuum up and place in suitable containers for future disposal. Only use vacuum cleaners approved for dust collection. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Outside or detached storage is preferred. Inside storage should be in a standard flammable storage cabinet. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 4 of 10

Nylon 12 Tough

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Trade Secret	Trade Secret	8-Hour TWA: 3 mg/m³ (inhalable particulate matter)
NIOSH	Trade Secret	Trade Secret	REL-TWA: 3.5 mg/m³ (up to 10 hr)
	Trade Secret	Trade Secret	IDLH: 1750 mg/m³
	Trade Secret	Trade Secret	REL-TWA: 0.1 mg/m³ (in the presence of polycyclic aromatic hydrocarbons [up to 10 hr])
OSHA	Trade Secret	Trade Secret	8-Hour TWA-PEL: 3.5 mg/m ³
United States(California)	Trade Secret	Trade Secret	8-Hour TWA-PEL: 3.5 mg/m ³

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

This product is a combustible material which may be ignited by friction, heat, sparks or flames. It is recommended that all dust control equipment (such as local exhaust ventilation and material transport systems) involved in handling this product contain explosion relief vents or an explosion suppression system. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area. Keep static electricity under control, which includes the bonding and grounding of equipment. Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 5 of 10

Nylon 12 Tough

other circumstances where air purifying respirators may not provide adequate protection.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Black powder
Odor	None
Odor threshold	Not determined or not available.
рН	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, static discharge, ignition sources, dust generation and accumulation and incompatible materials.

Incompatible Materials:

None known.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 6 of 10

Nylon 12 Tough

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Trade Secret	oral	LD50 Rat: >2000 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >4.6 mg/L (4 hr [dust])

Skin Corrosion/Irritation

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available. **Serious Eye Damage/Irritation**

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available. **Respiratory or Skin Sensitization**

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Species	Result
Trade Secret	Not applicable	Suspected of causing cancer by inhalation exposure route.

International Agency for Research on Cancer (IARC):

Name	Classification
Trade Secret	Group 2B
	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Trade Secret	Known to be human carcinogens
	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 7 of 10

Nylon 12 Tough

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available. Other Information: No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result	
Trade Secret	Fish LC50 Danio rerio: >1000 mg/L (96 hr)	
	Aquatic Plants EC50 Raphidocelis subcapitata: >100 mg/L (72 hr [growth rate and cell number])	
	Aquatic Invertebrates EC50 Daphnia magna: >100 mg/L (48 hr [immobilisation and toxicity])	

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 8 of 10

Nylon 12 Tough

Name	Result
	Aquatic Invertebrates EC50 Daphnia magna: 4.9 mg/L (16 d [immobilization; QSAR])

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
	Persistence assessment based on biodegradability is not relevant for
	inorganic compounds such as this substance.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
	Bioaccumulation assessment using a classic BCF assessment is not considered relevant for inorganic compounds such as this substance.

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result	
Trade Secret	Mobility in soil assessment based on KOC/Kd values are not relevant for	
	inorganic compounds such as this substance.	

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB** assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Trade Secret	PBT assessment does not apply to inorganic compounds such as this substance.
vPvB assessment:	
Trade Secret	vPvB assessment does not apply to inorganic compounds such as this substance.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

As supplied, this material is not considered a hazardous waste under RCRA. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Do not discharge into public wastewater or surface waters. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

Contaminated packages:

Dispose contaminated packages in a safe manner in accordance with local and national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 9 of 10

Nylon 12 Tough

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals: None of the ingredients are listed.

CERCLA: None of the ingredients are listed. **RCRA:** None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

Trade Secret	Trade Secret	Listed

New Jersey Right to Know:

Trade Secret Listed

New York Right to Know: None of the ingredients are listed.

Pennsylvania Right to Know:

Trade Secret	Trade Secret	Listed
--------------	--------------	--------

California Proposition 65:

▲WARNING: This product can expose you to Carbon black (airborne, unbound particles of respirable size); which is known to the State of California to cause cancer. For more information go to

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 09.09.2024 Page 10 of 10

Nylon 12 Tough

www.P65Warnings.ca.gov

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0 **HMIS:** 0-0-0

Initial Preparation Date: 09.09.2024

End of Safety Data Sheet